MATERIAL SAFETY DATA SHEET

Product and Company Identification

CHEMICAL SOLUTIONS

A Division of Superior Solutions Ltd.

851 Progress Court, Oakville, Ontario Canada L6L 6K1

Tel: 1-800-921-5527 www.superiorsols.com

Product Name: SANY ZOE ODOR NEUTRALIZER

Codes: ZOE-ORD-710

Material Uses: Industrial applications: Air and textile deodorant

24-Hr Emergency Tel: CANUTEC (613) 996-6666 or *666 (on a cellular phone)

Hazardous Ingredients

Isopropyl Alcohol 67-63-0 3 - 5%

Physical Data

Ingredients

Physical State: Clear sparkling liquid

Color: Yellow orange Odor: Citrus

Odor Threshold: The highest known value is 40

ppm (Isopropyl Alcohol) **pH:** 4.1 - 4.4 (as is) Volatility: NA

Evaporation Rate: As water

Freezing Point: May start to solidify at 0°C

(32°F) based on data for water

Boiling Point: NA

Specific Gravity: 1.01 (Water = 1)

Vapor Density: NA Vapor Tension: NA

Log Kow: The product is more soluble in water.

Ionicity (Surface Active Agent): Anionic

Critical Temperature: NA Instability Temperature: NA Conditions of Instability: NA

Dispersion Properties: See solubility in water,

methanol, diethyl ether, n-octanol, **Solubility:** Completely soluble in water.

Fire and Explosion Data

Flammability: Combustible

Auto-Ignition Temperature: The lowest known value is 389.89°C (750°F) (Isopropyl alcohol) **Products of Combustion:** Carbon oxides (CO.

CO₂), nitrogen oxides (NO, NO₂)

Flash Point: NA

Flammable Limits: Lower: 2%, Upper: 12%

(Isopropyl alcohol)

Extinguishing Media: Flammable liquid, soluble

or dispersed in water.

Small Fire: Use dry chemical powder.

Large Fire: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, auto-ignition or

explosion.

Flammability of the Product: Flammable in

Manufacturer:

PRODUITS SANY

830 rue St-Pierre Sud Joliette,

% wt.

Que. J6E 8R7

E-mail: info@sanyinc.com Tel: 1-800-363-2776

HEALTH FLAMMABILITY	1	0 – Insignific 1 – Slight 2 – Moderate 3 – High 4 – Extreme
REACTIVITY	1	
PERSONAL PROTECTION	В	

0 - Insignificant 1 – Slight 2 - Moderate









Acute: 16970 ppm 4 hrs (Rat), 37476 mg/m³ Acute: 3600 mg/kg (Oral, Mouse), 5045 mg/kg (Oral, 8 hrs (Mouse), 66100 mg/m³ 8 hrs (Rat) Rat), 12800 mg/kg (Dermal, Rabbit)

presence of open flames and sparks, heat, and/or oxidizing materials. Slightly flammable to flammable in presence of combustible materials.

CAS#

Risks of Explosion: Risks of explosion of the product in presence of mechanical impact: NA Risks of explosion of the product in presence of

static discharge: NA

Reactivity

Stability: Stable

Hazardous Decomposition Products: NA

Degradability: NA

Products of Degradation: NA

Corrosivity: NA

Reactivity: Slightly reactive to reactive with

oxidizing agents, acids.

Instability Temperature: NA

Conditions of Instability: Stable under normal

conditions. Does not polymerize.

First Aid Measures

Eves: Check for and remove any contact lenses. Immediately flush with running water for at least 15 minutes, keeping eyelids open. Use temperate

water. Get medical attention.

Skin: Wash immediately with soap and plenty of temperate water. If irritation develops, seek

medical attention.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

Preventive Measures

Small Spills and Leaks: Dilute with water and

mop up or absorb with an inert dry material and place in an appropriate waste disposal container.

Personal Protective Equipment (Small Spills and Leaks): Safety glasses, Lab coat, Vapor respirator. Be sure to use an approved/certified respirator or

equivalent. Gloves (impervious).

Large Spills and Leaks: Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local

Personal Protective Equipment (Large Spills and Leaks): Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient: consult a specialist BEFORE handling this product.

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Precautions: Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. If ingested, seek medical advice immediately and show the container or the label.

Storage: Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). KEEP OUT OF REACH OF CHILDREN.

Handling: Keep away from heat, sparks and

flame. Keep container closed. Use only with adequate ventilation. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.

Waste Disposal: Waste must be disposed of in accordance with municipal, provincial and federal

regulations.

Special Shipping Information: NA

Toxicological Information

Routes of Entry: Inhalation, Ingestion TLV: Isopropyl alcohol

TWA: 400 (ppm) from ACGIH (TLV) [United]

States] [1993]

TWA: 400 (ppm) from OSHA (PEL) [United

STEL: 500 from ACGIH (TLV) [United States] CEIL: 1230 (mg/m3) from ACGIH (TLV) [United

STEL: 500 (ppm) from OSHA (PEL) [United States]

Consult local authorities for acceptable exposure

Toxicity to Animals: Acute oral toxicity (LD50): 34195 mg/kg [Rat]; Acute dermal toxicity (LD50): 256000 mg/kg (Rabbit) (Calculated value for the mixture).

Acute Effects on Humans: Slightly hazardous in case of skin contact (sensitizer).

Chronic Effects on Humans: Repeated or prolonged exposure is not known to aggravate medical condition under normal use.

Synergistic Products (Toxicologically): NA

Skin Irritation/Corrosivity: NA

Sensitization: Slightly hazardous in case of skin contact (sensitizer).

Carcinogenic Effects: NA

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Toxicity to Reproductive System: NA

Teratogenic Effect: NA Mutagenic Effect: NA

Regulatory Information
TDG Road/Rail: Class 3.3: Flammable liquid with a flash point between 23°C (73°F) and 61°C (142°F). According to article 1.17 of TDG regulation, this product might be exempted for limited quantities.

Limited Quantity: 5L
Shipping Name: FLAMMABLE LIQUID, N.O.S.
(Isopropyl alcohol), UN1993 PG III

WHMIS: Class B3 D2B

Preparation Information

Prepared By: GreenLABS QA & Control

Date: March 15, 2016 **Revised:** May 25, 2016 **Tel:** 1-800-921-5527

NA = Not available

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.