



ANMO

ANTI-FOAM

DEFOAMING AGENT

ANTI-FOAM has been specially formulated to eliminate and reduce foam in the reservoir tanks of commercial and industrial equipment used to pick up water. It is ideal for use in carpet cleaning equipment, wet vacs and scrubbers.



ANMO-4S4

ANMO ANTI-FOAM DEFOAMING AGENT

DIRECTIONS FOR USE

Automatic Scrubbers / Shampoo Machines: Pour directly into the recovery tank. Use 6 to 12 ml per 4L of recovery capacity. If foam is excessive use up to 25 ml per 4L.

Hot Water Extractors: To prevent the suds from blocking the unit mix 1 part product to 80 parts water and lightly spray the carpet before cleaning. Also spray a small amount of defoamer into the unit filter.

DILUTION RATIOS

Task	Mop	Spray	Auto-scrubber
Light	1:550	-	-
Medium	1:285	-	1:80
Heavy Duty	-	1:160	-

Description

Physical State and Appearance	Clear, transparent liquid
Color	Yellow
Sediment	None
Odor	Pine
pH (concentrated)	11.00 – 11.50
Specific Gravity	1.020 – 1.04
Flash Point	None

SAFETY REMINDER

Before using this product please ensure employees read and understand the product labels and Material Safety Data Sheet. Directions for use can be found on the label as well as the MSDS. Additionally, employees can find hazard warnings, precautionary statements and first aid procedures on the MSDS sheets. MSDS are available online at greenlabscs.com or by calling 1-800-921-5527. Improper use may result in damage or injury.

Product Code	Package Size
ANMO-4S4	4 X 4L Bottles

Your Partner In Making Sustainable Healthy Environments

We are committed to ensuring our cleaning solutions make your workplace clean, green and healthy – while reducing costs, enhancing employee safety, and promoting the sustainability of your cleaning, facility care and sanitation process.

