



GLF-411 X-TREM FLOOR FINISH

GLF-411 X-TREM is a floor finish with an extremely resistant metallic, acrylic copolymer base. It can be used on all types of flooring like sealed wood, marble and terrazzo. It spreads evenly, does not fade and is easily maintained.

FEATURES, ADVANTAGES AND BENEFITS

- Delivers excellent gloss build
- Provides outstanding durability
- Dramatic response to propane, battery and electric equipment
- Can be used on all types of flooring



GLF-411-10S2

GLF-411 X-TREM FLOOR FINISH

DIRECTIONS FOR USE

Strip the old floor finish, wash with a neutral detergent and rinse with clear water and allow to dry. Apply a first, thin and even layer with a wax applicator or a fine string mop. Allow the first layer to dry and harden before applying the second. Allow to harden for 24 hours, then polish the surface with a polisher. For daily maintenance of the finish, clean the surface with a neutral detergent like GLF-401.

DILUTION RATIOS

No dilution required.

Description	
Physical State and Appearance	Opaque liquid
Color	White
Sediment	None
Odor	Characteristic
pH (concentrated)	8.50 – 8.80
Specific Gravity	1.020 – 1.025
Flash Point	None

SAFETY REMINDER

Before using this product please ensure employees read and understand the product labels and Material Safety Data Sheet. Directions for use can be found on the label as well as the MSDS. Additionally, employees can find hazard warnings, precautionary statements and first aid procedures on the MSDS sheets. MSDS are available online at greenlabscs.com or by calling 1-800-921-5527. Improper use may result in damage or injury.

Product Code	Package Size
GLF-411-4S4	4 X 4L Bottles
GLF-411-10S2	2 X 10L Bottles

Your Partner In Making Sustainable Healthy Environments

We are committed to ensuring our cleaning solutions make your workplace clean, green and healthy – while reducing costs, enhancing employee safety, and promoting the sustainability of your cleaning, facility care and sanitation process.

